

STUDWORK AND WALL THICKNESS

RDF FRAME THICKNESS	YOUR STUD THICKNESS	YOU WANT A FINISHED WALL THICKNESS OF.....	PLASTERBOARDING		EXTRA INFORMATION		
			ON THE POCKET (each side)	ON THE STUD (each side)	Jamb Kit Reference	Recommendations	
T I M B E R & M E T A L S T U D	70mm	63mm CLS	95mm	One 12.5mm layer	6mm layer (One side only) & One 12.5 mm layer	95	Not recommended for tiling
			120mm	Two 12.5mm layer	6mm layer (One side only) & Two 12.5 mm layer	125	Not Suitable for 44mm doors
			125mm (5")	One 12.5mm layer & One 15mm layer	6mm Layer (One side only) & One 12.5 mm layer & One 15mm layer	125	Recommended for Tiling
		70mm STEEL	95mm	One 12.5mm layer	One 12.5mm layer	95	Not recommended for tiling
			120mm	Two 12.5mm layer	Two 12.5 mm layer	125	Not Suitable for 44mm doors
			125mm (5")	One 12.5mm layer & One 15mm layer	One 12.5 mm layer & One 15mm layer	125	Recommended for Tiling
	100mm	125mm (5")	One 12.5mm layer & One 15mm layer	12.5mm Layer	125	Recommended for Tiling	